# **CEWELD®**

## L-Ag55Sn

CATEGORY	Brazing									
TYPE	High silver containing cadmium free brazing alloy.									
APPLICATIONS	Joining: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also suitable for dissimilar joints between these metals. Do not use this alloy above working temperatures of 200°C									
PROPERTIES	High silver containing universal silver brazing alloy without cadmium with low operating temperature and high mechanical properties. Due to the addition of Sn. this alloy will show a bright looking joint and is more capillary then the standard silver brazing alloys.									
CLASSIFICATION	AWS A 5.8: BAg-7 EN ISO 1044: AG 102 DIN 8513: L-Ag55Sn									
SUITABLE FOR	Brazing: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also suitable for dissimilar joints between these metals.									
APPROVALS	CE approved									
WELDING POSITIONS:	PA PB PC PC PC PC PF PF PG									

#### FILLER METAL ANALYSIS %

Ag	Cu	Zn	Sn
55	22	17	5

#### **MECHANICAL PROPERTIES**

Heat	Ī	R <sub>P0,2</sub>		Rm	Ī	Weight		Operating temperature	Impact En	ergy (J) ISO-V	Melting range
Treatment	i	$(N/mm^2)$	i	$(N/mm^2)$	Ī	g/cm <sup>3</sup>		°C	-40°C	-60°C	°C
As brazed				400		9.5	-	650			620-650

### **BRAZING PARAMETERS / PACKING**

Welding Parameters			Flame type Optimum brazing			Packing			
D (mm)	Length (mm)		Adjustment		Gab (mm)	kg / tube / carton	kg / spools		
1.5	500		Neutral		0.01-0.25	1/5/20	1 till 10		
2.0	500	i	Neutral		0.01-0.25	1/5/20	1 till 10		
3.0	500		Neutral		0.01-0.25	1/5/20	1 till 10		

OTHER DELIVERY FORMS Flux coated rods (F), endless wire on spools and customized brazing rings.